Small Block Chevy 4-Valve Pocket Flat Top POWERPAK Piston Set





Cubic	Bore	Stroke	Rod	Comp	Pin	Crown	Wght	Compression		ion	Alloy	Clearance Guide			
Inche	S			Height	Diam.	Vol	G		Ratio			Meas.	Min	Max	Part No.
SMA	SMALL BLOCK CHEVY 4-VALVE POCKET FLAT TOP														
1.0, 1	.0, 2.0mr	n File Fit Perfo	rmance Rin	g Set inclu	uded			58cc	64cc	70cc					
355	4.030	3.480/3.500	5.700	1.550	0.927	-5.0cc	495	11.0	10.2	9.6	4032	0.500	0.0025	0.0033	930203630
357	4.040						499	11.0	10.3	9.6					930203640
360	4.060						507	11.1	10.3	9.7					930203660
355	4.030	3.480/3.500	6.000	1.250	0.927	-5.0cc	454	11.0	10.2	9.6	4032	0.500	0.0025	0.0033	930203730

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt. "Min" and "Max" is the suggested range of clearance over the coating for each application. **Compression Ratio -** calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

