

# Small Block Ford Inverted Dome PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide			Part No.
								58cc	64cc	70cc		Meas.	Min	Max	
<b>SMALL BLOCK FORD INVERTED DOME</b>															
<b>1.0, 1.0, 2.0mm File Fit Performance Ring Set Included</b>															
393	4.030	3.850	5.956	1.600	0.912	-26cc	469	9.7	9.2	8.7	4032	0.500	0.0025	0.0033	930248130
395	4.040						473	9.8	9.2	8.7					930248140
408	4.030	4.000	6.200	1.300	0.927	-20cc	431	10.7	10.1	9.5	2618	0.500	0.0046	0.0054	930249330 *
410	4.040						435	10.7	10.1	9.5					930249340 *
408	4.030						418	10.7	10.1	9.5	4032	0.500	0.0025	0.0033	930248230
410	4.040	422	10.7	10.1	9.5	930248240									
408	4.030						-28cc 446	9.9	9.3	8.9	2618	0.500	0.0046	0.0054	930249430 *
408	4.030	433	9.9	9.3	8.9	4032	0.500	0.0025	0.0033	930248330					
428	4.125	4.000	6.250	1.245	0.927	-17cc	418	11.5	10.8	10.1	4032	0.500	0.0025	0.0033	930248625
434	4.155						429	11.6	10.9	10.3					930248655
408	4.030						-26cc 434	10.1	9.5	9.0	2618	0.500	0.0046	0.0054	930249530 *
410	4.040	438	10.1	9.5	9.0	930249540 *									
408	4.030						422	10.1	9.5	9.0	4032	0.500	0.0025	0.0033	930248430
410	4.040	426	10.1	9.5	9.0	930248440									
428	4.125						448	10.4	9.9	9.4	2618	0.500	0.0046	0.0054	930249625 *
428	4.125	435	10.4	9.9	9.4	4032	0.500	0.0025	0.0033	930248525					
434	4.155						447	10.6	10.0	9.5	4032	0.500	0.0025	0.0033	930248555
438	4.125	4.100	6.200	1.245	0.927	-17cc	418	11.7	11.0	10.4					4032
445	4.155						429	11.9	11.1	10.5	930248655				
418	4.030						-26cc 434	10.3	9.7	9.2	2618	0.500	0.0046	0.0054	930249530 *
420	4.040	420	10.3	9.8	9.2	930249540 *									
418	4.030						422	10.3	9.7	9.2	4032	0.500	0.0025	0.0033	930248430
420	4.040	426	10.3	9.8	9.2	930248440									
438	4.125						448	10.7	10.1	9.6	2618	0.500	0.0046	0.0054	930249625 *
438	4.125	435	10.7	10.1	9.6	4032	0.500	0.0025	0.0033	930248525					
408	4.030	4.000	6.250	1.230	0.927	-20cc	409	10.7	10.1	9.5	4032	0.500	0.0025	0.0033	930248730
410	4.040						413	10.7	10.1	9.5					930248740
332	4.030	3.250	5.400	1.165	0.927	-16cc	411	9.2	8.7	8.2	2618	0.500	0.0046	0.0054	930249930 *
333	4.040						415	9.3	8.7	8.2					930249940 *
332	4.030						399	9.2	8.7	8.2	4032	0.500	0.0025	0.0033	930248830
333	4.040	403	9.3	8.7	8.2	930248840									
347	4.125						422	9.6	9.0	8.5	2618	0.500	0.0046	0.0054	930247725 *
353	4.155	433	9.7	9.1	8.6	930247755 *									
347	4.125						410	9.6	9.0	8.5	4032	0.500	0.0025	0.0033	930245025
353	4.155	421	9.7	9.1	8.6	930245055									
426	4.030	4.170	6.250	1.165	0.927	-16cc	411	11.6	10.9	10.2	2618	0.500	0.0046	0.0054	930249930 *
428	4.040						415	11.6	10.9	10.3					930249940 *
426	4.030						399	11.6	10.9	10.2	4032	0.500	0.0025	0.0033	930248830
428	4.040	403	11.6	10.9	10.3	930248840									
446	4.125						422	12.0	11.3	10.6	2618	0.500	0.0046	0.0054	930247725 *
452	4.155	433	12.2	11.4	10.8	930247755 *									
446	4.125						410	12.0	11.3	10.6	4032	0.500	0.0025	0.0033	930245025
452	4.155	421	12.2	11.4	10.8	930245055									
347	4.030	3.400	5.400	1.090R	0.927	-16cc	395	9.6	9.0	8.5	2618	0.500	0.0046	0.0054	930247830 *
349	4.040						398	9.7	9.1	8.6					930247840 *
347	4.030						384	9.6	9.0	8.5	4032	0.500	0.0025	0.0033	930249130
349	4.040	387	9.7	9.1	8.6	930249140									
364	4.125						407	10.0	9.4	8.9	2618	0.500	0.0046	0.0054	930247925 *
364	4.125	395	10.0	9.4	8.9	4032	0.500	0.0025	0.0033	930249025					

Compression Heights with "R" INCLUDE Oil Support Rails

\*Available In Multiple Alloys

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

