

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.		
										Meas.	Min	Max			
BIG BLOCK CHEVY FLAT TOP (TALL DECK 10.200)															
1.5, 1.5, 3.0mm File Fit Performance Ring Set Included								112cc	118cc	124cc					
573	4.500	4.500	6.535	1.395	0.990	-3.4cc	542	10.3	9.9	9.5	4032	0.600	0.0041	0.0049	928906700
598	4.600						565	10.7	10.3	9.9					928906701
489	4.280	4.250	6.800	1.270R	0.990	-3.4cc	469	9.0	8.7	8.3	4032	0.250	0.0041	0.0049	929869580
496	4.310						481	9.1	8.8	8.4					929869510
498	4.320						485	9.2	8.8	8.5					929869520
505	4.350						498	9.3	8.9	8.5					929869550
541	4.500					-3.4cc	518	9.8	9.4	9.0	4032	0.445	0.0041	0.0049	928957000
555	4.560						544	10.0	9.6	9.2					928957060
565	4.600						562	10.2	9.8	9.4					928957001
518	4.280	4.500	6.660	1.270R	0.990	-3.4cc	469	9.0	8.7	8.3	4032	0.250	0.0041	0.0049	929869580
525	4.310						481	9.1	8.8	8.4					929869510
528	4.320						485	9.2	8.8	8.5					929869520
535	4.350						498	9.3	8.9	8.5					929869550
573	4.500					-3.4cc	518	9.8	9.4	9.0	4032	0.445	0.0041	0.0049	928957000
588	4.560						544	10.0	9.6	9.2					928957060
598	4.600						562	10.2	9.8	9.4					928957001
632	4.600	4.750	6.660	1.160R	0.990	-3.4cc	519	11.2	10.8	10.4	4032	0.375	0.0041	0.0049	929908801

Compression Heights with "R" INCLUDE Oil Support Rails



Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.
 "Min" and "Max" is the suggested range of clearance over the coating for each application.
Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted.