## Duramax PowerPak Piston Sets



Cubic	c Bore	Stroke	Rod	Comp	Comp Pin	Crown	Wght	Compression	Alloy	Clearance Guide			
Inche	S			Height	Diam.	Vol	G	Ratio		Meas.	Min	Max	Part No.
GM 6	6.6L Dura	max Cast Pe	rformance	Pistons									
					berforma	nce bow	l desiar	n, coated skirt - Ring	ı Set (40x	xMDK-D)	Include	d	
		10" - Fits LB7,		_					,	······································			
		vith 0.012" pist		•		.037 x 4.	115" he	ad gasket					
								6.5cc					
403	4.055	3.898	6.417	1.951	1.358	-40.7cc	864	16.6	M142	0.500	0.0016	0.0023	930036055
407	4.075						880	16.8					930036075
411	4.095						896	17.0					930036095

## GM 6.6L Duramax Cast Performance Pistons w/ 0.075" Deep Valve Pockets

Revised casting with improved crown geometry and performance bowl design, coated skirt - Ring Set (40xxMDK-D) Included CH reduced 0.010" - Fits LB7, LLY, LBZ, LMM, LGH, LML

CR calculated with 0.012" piston protrusion above deck and 0.037 x 4.115" head gasket												
							6.5cc					
4.055	3.898	6.417	1.951	1.358	-41.8cc	861	16.3	M142	0.500	0.0016	0.0023	930029855
4.075						877	16.5					930029875
4.095						893	16.6					930029895
	4.055 4.075	4.055 3.898 4.075	4.055 3.898 6.417 4.075	4.055 3.898 6.417 1.951 4.075	4.0553.8986.4171.9511.3584.075 </td <td>4.055 3.898 6.417 1.951 1.358 -41.8cc 4.075</td> <td>4.055 3.898 6.417 1.951 1.358 -41.8cc 861 4.075 877</td> <td>4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3   4.075        16.5</td> <td>4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3 M142   4.075     877 16.5</td> <td>4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3 M142 0.500   4.075 0 <td< td=""><td>6.5cc   4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3 M142 0.500 0.0016   4.075 75 76 7</td><td>6.5cc   4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3 M142 0.500 0.0016 0.0023   4.075 0</td></td<></td>	4.055 3.898 6.417 1.951 1.358 -41.8cc 4.075	4.055 3.898 6.417 1.951 1.358 -41.8cc 861 4.075 877	4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3   4.075        16.5	4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3 M142   4.075     877 16.5	4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3 M142 0.500   4.075 0 <td< td=""><td>6.5cc   4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3 M142 0.500 0.0016   4.075 75 76 7</td><td>6.5cc   4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3 M142 0.500 0.0016 0.0023   4.075 0</td></td<>	6.5cc   4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3 M142 0.500 0.0016   4.075 75 76 7	6.5cc   4.055 3.898 6.417 1.951 1.358 -41.8cc 861 16.3 M142 0.500 0.0016 0.0023   4.075 0

GM 6.6L Duramax Forged Aluminum Race Pistons w/ 0.075" Deep Valve Pockets Shelf stock version of the Custom Race Piston, Coated skirt and Hard Anodized top ring groove - Ring Set (40xxMDR\*) Included CH reduced 0.010" - Fits LB7, LLY, LBZ, LMM, LGH, LML - Brodix and Wagler Cylinder Heads CR calculated with 0.012" piston protrusion above deck and 0.037 x 4.115" head gasket

							6.5CC					
403	4.055	3.898	6.417	1.951	1.358 -4	41.8cc 774	16.3	M124P	0.500	0.0055	0.0063	930036255
407	4.075					785	16.5					930036275
411	4.095					797	16.6					930036295
				· -		-		-			-	

\*Includes CrN PVD Stainless Steel 1/16 Rectangular Top Ring

GM 6.6L Duramax Forged Aluminum Race Pistons (Custom Order)													
Call f	Call for details. Coated skirt and Hard Anodized top ring groove - Ring Set (40xxMDR*) Included												
403	4.055	Made To Order	Made To Order	Made To Order	M124P	0.500	0.0055	0.0063	929946655				
407	4.075								929946675				
411	4.095								929946695				

\*Includes CrN PVD Stainless Steel 1/16 Rectangular Top Ring

Have more questions about this product?



## Contact MAHLE Motorsport at 888-255-1942

**Motorsport**