

Ford Modular 5.4L 2-Valve or 4-Valve PowerPak

Cubic Bore Inches	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide Meas.	Min	Max	Part No.			
FORD MODULAR 5.4 2-VALVE or 4 VALVE															
1.0, 1.0, 2.0mm File Fit Performance Ring Set included															
CR calculated at 0.118" below deck and 0.040" head gasket thickness															
							42cc	46cc	52cc						
330	3.552	4.165	6.657	1.220	0.866	-16.0cc	356	9.1	8.7	8.2	M142P	0.500	0.0006	0.0014	930256052
334	3.572						363	9.1	8.8	8.3					930256072
336	3.582						367	9.2	8.8	8.3					930256082
334	3.572					-22.0cc	374	8.6	8.3	7.8	2618	0.500	0.0025	0.0033	930256172 *
330	3.552					0cc	392	11.0	10.4	9.7	M142P	0.500	0.0006	0.0014	930256252
334	3.572						399	11.1	10.5	9.8					930256272

***PowerPak Plus 2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications.**

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942