

GM 604 Crate Engine Drop-In PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide			Part No.
								58cc	64cc	70cc		Meas.	Min	Max	

GM 604 Crate Engine Drop-In Forged Replacement - PRESS-FIT Pin

Requires 2.0, 1.5, 4.0mm Ring Set (Not Included)

								58cc	64cc	70cc					
350	4.000	3.480	5.700	1.559	0.927	-4.9cc	548	11.1	10.3	9.6	4032	0.500	0.0047	0.0051	930127800
350	4.002						549	11.1	10.3	9.6					930127802
351	4.005						550	11.1	10.3	9.6					930127805
351	4.008						552	11.1	10.3	9.7					930127808
353	4.020						557	11.2	10.4	9.7					930127820
355	4.030						561	11.2	10.4	9.7					930127830

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

MAHLE
Motorsport