

# Hemi 5.7L Dome PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide Meas.		Part No.
												Min	Max	

**HEMI 5.7L - compatible with all 5.7L and 6.1L heads**

**1.0, 1.0, 2.0mm File Fit Performance Ring Set Included**

**CR calculated at 0.016" below deck and 0.027" head gasket thickr 65cc 74cc 85cc**

345	3.917	3.579	6.242	1.205	0.927	10.2cc	438	12.2	10.8	9.5	2618	0.500	0.0036	0.0044	930276017 *									
347	3.927						442	12.2	10.8	9.5					930276027 *									
349	3.937						445	12.3	10.9	9.6					930276037 *									
350	3.947						448	12.3	10.9	9.6					930276047 *									
366	3.917	3.800	6.125	1.205	0.927	10.2cc	438	12.6	11.2	9.9	2618	0.500	0.0036	0.0044	930276017 *									
368	3.927						442	12.7	11.3	9.9					930276027 *									
370	3.937						445	12.7	11.3	10.0					930276037 *									
372	3.947						448	12.8	11.3	10.0					930276047 *									
392	3.927						4.050	6.125	1.095R	0.927					-2.2cc	405	11.6	10.5	9.4	4032	0.250	0.0025	0.0033	930276227
394	3.937															408	11.7	10.5	9.4					930276237
396	3.947	411	11.7	10.6	9.5	930276247																		
392	3.927	426	12.9	11.5	10.2	4032					0.250	0.0025	0.0033	930276327										
394	3.937	429	13.0	11.6	10.2	930276337																		
396	3.947	432	13.0	11.6	10.3	930276347																		

Compression Heights with "R" INCLUDE Oil Support Rails

\*Hard Anodized Top Ring Groove For Extreme Duty Applications

3.800 / 6.125 CR calculated at 0.022" below deck and 0.027" head gasket thickness

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

**MAHLE**  
Motorsport