

| Cubic<br>Inches | Bore | Stroke | Rod | Comp<br>Height | Pin<br>Diam. | Crown<br>Vol | Wght<br>G | Compression<br>Ratio | Alloy | Clearance Guide |     |     | Part No. |
|-----------------|------|--------|-----|----------------|--------------|--------------|-----------|----------------------|-------|-----------------|-----|-----|----------|
|                 |      |        |     |                |              |              |           |                      |       | Meas.           | Min | Max |          |

HEMI 6.2/6.4L BGE Stroker - 9.28 Deck Height

Also works with 6.1L CYLINDER HEAD

NOTE : Piston oil squirter removal and block-off is required w/ 4.050" crank due to conrod contact with OE squirter

1.0, 1.0, 2.0mm File Fit Performance Ring Set included

|     |       |       |       |        |       |       |     |      |      |       |        |        |            |
|-----|-------|-------|-------|--------|-------|-------|-----|------|------|-------|--------|--------|------------|
|     |       |       |       |        |       |       |     | 74cc |      |       |        |        |            |
| 426 | 4.091 | 4.050 | 6.125 | 1.125R | 0.927 | -15cc | 467 | 9.9  | 2618 | 0.500 | 0.0046 | 0.0054 | 930278191* |
| 427 | 4.095 |       |       |        |       |       | 469 | 10.0 |      |       |        |        | 930278195* |
| 428 | 4.100 |       |       |        |       |       | 471 | 10.0 |      |       |        |        | 930278100* |

Compression Heights with "R" INCLUDE Oil Support Rails

\*Hard Anodized Top Ring Groove For Extreme Duty Applications



**Meas.** = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.  
"Min" and "Max" is the suggested range of clearance over the coating for each application.  
**Compression Ratio** - calculated at zero deck and 0.040" gasket unless otherwise noted.