

## Honda S2000 F22C 2.2L PowerPak Piston Set



| Bore   | Stroke | Rod      | Comp Height | Pin Diam. | Crown Vol      | Wght G     | Compression Ratio | Alloy       | Clearance Guide |               |               | Part No.           |
|--|--------|----------|-------------|-----------|----------------|------------|-------------------|-------------|-----------------|---------------|---------------|--------------------|
|  |        |          |             |           |                |            |                   |             | Meas.           | Min           | Max           |                    |
| <b>HONDA S2000 F22C 2.2L GOLD SERIES - FOR USE IN FACTORY FRM (FIBER REINFORCED MATRIX) CYLINDERS ONLY</b> |        |          |             |           |                |            |                   |             |                 |               |               |                    |
| 1.2, 1.2, 2.8mm Performance Ring Set Included, Designed for Aftermarket Rods                               |        |          |             |           |                |            |                   |             |                 |               |               |                    |
| CR calculated at 1.0mm above deck and 0.76mm head gasket thickness   |        |          |             |           |                |            |                   |             |                 |               | 54cc          |                    |
| 87.00mm  | 90.7mm | 149.65mm | 30mm        | 23mm      | 9.0cc          | 331        | 13.4              | 4032        | 0.375           | 0.0006        | 0.0014        | 929986125 **       |
| 87.25mm  |        |          |             |           |                |            |                   |             |                 |               |               |                    |
| <b>87.00mm</b>   |        |          |             |           | <b>-11.0cc</b> | <b>303</b> | <b>9.5</b>        | <b>2618</b> | <b>0.375</b>    | <b>0.0016</b> | <b>0.0024</b> | <b>929986425 *</b> |
| 87.25mm  |        |          |             |           |                | 306        | 9.5               |             |                 |               |               | 929986435 *        |

\*2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications

\*\*Hard Anodized Top Ring Groove For Extreme Duty Applications

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

**MAHLE**  
Motorsport