

L83 5.3L DI Drop-In PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Meas.	Guide Min	Max	Part No.
--------------	------	--------	-----	-------------	-----------	-----------	--------	-------------------	-------	-----------------	-----------	-----	----------

L83 5.3L DI DROP-IN FORGED REPLACEMENT ASSEMBLY NO BALANCING, NO COMP RATIO CHANGE 1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

CR calculated at 0.007" below deck and 0.051" head gasket thickness								57cc					
325	3.780	3.622	6.098	1.324	0.943	3.9cc	474	11.5	4032	0.500	0.0025	0.0033	930229880
327	3.790						478	11.6					930229890
329	3.800						482	11.6					930229800

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.
 "Min" and "Max" is the suggested range of clearance over the coating for each application.
Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

