

LS 5.3L Flat Top PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Meas.	Guide Min	Guide Max	Part No.
--------------	------	--------	-----	-------------	-----------	-----------	--------	-------------------	-------	-----------------	-----------	-----------	----------

LS 5.3L FLAT TOP - compatible with LS1/2/6 style cathedral port heads

1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

62cc 65cc 71cc

325	3.780	3.622	6.098	1.330	0.945	-4.2cc	421	10.1	9.7	9.1	2618	0.500	0.0036	0.0044	930218580 *
327	3.790						425	10.1	9.7	9.1					930218590 *
329	3.800						428	10.1	9.8	9.1					930218500 *
325	3.780	3.622	6.125	1.304	0.927	-4.2cc	407	10.1	9.7	9.1	4032	0.500	0.0025	0.0033	930217880
329	3.800						414	10.1	9.8	9.1					930217800
325	3.780						419	10.1	9.7	9.1					2618
327	3.790						423	10.1	9.7	9.1					930218890
329	3.800						427	1.0	9.8	9.1					930218800
325	3.780	3.622	6.125	1.299	0.927	-2.1cc	424	10.3	9.9	9.3	2618	0.500	0.0036	0.0044	930218480 **
327	3.790						428	10.4	10.0	9.3					930218490 **
329	3.800						431	10.4	10.0	9.4					930218400 **

*Available In Multiple Alloys

**2618 Alloy, Lateral Gas Ports, HD 0.0188"W Wrist Pin & Hard Anodized Top Ring Groove For Extreme Duty Applications

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

MAHLE
Motorsport