

# LS 6.0L & 6.2L Dome PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide Meas.	Min	Max	Part No.
--------------	------	--------	-----	-------------	-----------	-----------	--------	-------------------	-------	-----------------------	-----	-----	----------

**LS 6.0L & 6.2L DOME - compatible with LS3 / L92 rectangular port heads**

*(Check out our NEW LSX COMBO section for more LS3/L92 applications)*

1.0mm, 1.0mm, 2.0mm File Fit Performance Ring Set Included

70cc

365	4.005	3.622	6.125	1.314	0.927	2.0cc	470	10.8	4032	0.500	0.0025	0.0033	197719205
366	4.010					472	10.8	197719210					
370	4.030					480	10.9	197719230					
376	4.065					494	11.1	197719265					
377	4.070				496	11.1						197719270	
378	4.075				497	11.1							197719275
365	4.005	3.622	6.125	1.304	0.927	12.0cc	468	12.3	2618	0.500	0.0046	0.0054	197714805 *
366	4.010					470	12.3	197714810 *					
370	4.030					477	12.4	197714830 *					
376	4.065					490	12.6	197714865 *					
377	4.070					492	12.6	197714870 *					
378	4.075					494	12.6	197714875 *					

\*2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications

**Meas.** = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

**Compression Ratio** - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

**MAHLE**  
Motorsport