

# LS 6.0L Dish PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide			Part No.	
											Meas.	Min	Max			
<b>LS 6.0L DISH</b>																
<i>LSX COMBO pockets - compatible with LS1/2/6 style cathedral port heads &amp; LS3 / L92 style rectangular port heads</i>																
<b>1.0, 1.0, 2.0mm File Fit Performance Ring Set Included</b>											62cc	65cc	71cc			
364	4.000	3.622	6.125	1.304	0.927	-12.0cc	430	10.1	9.8	9.2	2618	0.500	0.0046	0.0054	930225400	
365	4.005						432	10.1	9.8	9.2					930225405	
366	4.010						434	10.1	9.8	9.2					930225410	
370	4.030						442	10.2	9.9	9.3					930225430	
403	4.005	4.000	6.125	1.110	0.927	-12.0cc	411	11.0	10.7	10.0	4032	0.500	0.0025	0.0033	930219305	
404	4.010						413	11.1	10.7	10.1					930219310	
408	4.030						421	11.2	10.8	10.2					930219330	
402	4.000			1.110R	0.927	-14.0cc	399	10.8	10.4	9.8	2618	0.500	0.0046	0.0054	930229400	
403	4.005	400	10.8				10.5	9.9	930229405							
404	4.010	402	10.8				10.5	9.9	930229410							
408	4.030	410	10.9				10.6	10.0	930229430							
402	4.000					-25cc	400	9.6	9.4	8.9	2618	0.500	0.0046	0.0054	930225500	
403	4.005	402	9.7	9.4	8.9		930225505									
404	4.010	404	9.7	9.4	8.9		930225510									
408	4.030	412	9.8	9.5	9.0		930225530									
415	4.000	4.125	6.125	1.050R	0.927	-20.0cc	388	10.4	10.1	9.6	2618	0.500	0.0046	0.0054	930230000	
416	4.005						390	10.4	10.1	9.6					930230005	
417	4.010						392	10.5	10.2	9.6					930230010	
421	4.030						400	10.5	10.2	9.7					930230030	

Compression Heights with "R" INCLUDE Oil Support Rails

**Meas.** = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

**Compression Ratio** - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

**MAHLE**  
Motorsport