

LS 6.2L Dish (LSA / LS9) PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Meas.	Guide Min	Max	Part No.
--------------	------	--------	-----	-------------	-----------	-----------	--------	-------------------	-------	-----------------	-----------	-----	----------

LS 6.2L DISH (LSA / LS9) - compatible with all LS Heads
 Designed for High Boost Applications w/ reduced CH and no valve pockets
 1.0, 1.0, 2.0mm File Fit Performance Ring Set Included
 CR calculated at 0.005" below deck and 0.051x4.100" head gasket

								64cc	69cc	72cc					
376	4.065	3.622	6.125	1.299	0.927	-4.5cc	478	10.6	10.0	9.7	2618	0.500	0.0046	0.0054	197813865 *
377	4.070						480	10.6	10.0	9.7					197813870 *
378	4.075						483	10.6	10.0	9.7					197813875 *
379	4.080						485	10.6	10.1	9.8					197813880 *

*2618 Alloy, HD 0.188"W H13 Wrist Pin & Hard Anodized Top Ring Groove For Extreme Duty Applications

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.
 "Min" and "Max" is the suggested range of clearance over the coating for each application.
Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

