

LS 6.2L Flat Top PowerPak Piston Set

Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide			Part No.	
LS 6.2L FLAT TOP																
LSX COMBO pockets - compatible with LS1/2/6, LS7, and LS3 / L92 style heads																
1.0, 1.0, 2.0mm File Fit Performance Ring Set Included											64cc	70cc	72cc			
376	4.065	3.622	6.098	1.330	0.945	-5.8cc	453	10.8	10.1	9.9	4032	0.500	0.0025	0.0033	930227765	
377	4.070						455	10.9	10.2	9.9					930227770	
378	4.075						457	10.9	10.2	10.0					930227775	
379	4.080						459	10.9	10.2	10.0					930227780	
376	4.065	3.622	6.125	1.304	0.927	-5.8cc	467	10.8	10.1	9.9	2618	0.500	0.0046	0.0054	930227065 *	
377	4.070						469	10.9	10.2	9.9					930227070 *	
378	4.075						471	10.9	10.2	10.0					930227075 *	
379	4.080						473	10.9	10.2	10.0					930227080 *	
376	4.065	4.000	6.125	1.110	0.927	-5.8cc	452	10.8	10.1	9.9	4032	0.500	0.0025	0.0033	930227865	
377	4.070						454	10.9	10.2	9.9					930227870	
378	4.075						456	10.9	10.2	10.0					930227875	
379	4.080						458	10.9	10.2	10.0					930227880	
376	4.065	4.000	6.125	1.110R	0.927	-5.8cc	466	10.8	10.1	9.9	2618	0.500	0.0046	0.0054	930226865 *	
377	4.070						468	10.9	10.2	9.9					930226870 *	
378	4.075						470	10.9	10.2	10.0					930226875 *	
379	4.080						472	10.9	10.2	10.0					930226880 *	
415	4.065	4.125	6.125	1.050R	0.927	-5.8cc	426	11.9	11.1	10.9	4032	0.500	0.0025	0.0033	930227965	
416	4.070						428	11.9	11.1	10.9					930227970	
417	4.075						430	11.9	11.1	10.9					930227975	
418	4.080						432	11.9	11.2	10.9					930227980	
415	4.065	4.125	6.125	1.050R	0.927	-5.8cc	437	11.9	11.1	10.9	2618	0.500	0.0046	0.0054	930227565 *	
416	4.070						439	11.9	11.1	10.9					930227570 *	
417	4.075						441	11.9	11.1	10.9					930227575 *	
418	4.080						443	11.9	11.2	10.9					930227580 *	
428	4.065	4.125	6.125	1.050R	0.927	-5.8cc	427	12.2	11.4	11.2	2618	0.500	0.0046	0.0054	930227265	
429	4.070						429	12.2	11.4	11.2					930227270	
430	4.075						431	12.3	11.5	11.2					930227275	
431	4.080						433	12.3	11.5	11.2					930227280	

Compression Heights with "R" INCLUDE Oil Support Rails

*Available In Multiple Alloys

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

MAHLE
Motorsport