

LS 5.7L & 6.0L Flat Top & Dish PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide			Part No.				
								Meas.	Min	Max									
LS 5.7L FLAT TOP & DISH - compatible with LS1/2/6 style cathedral port heads																			
1.0, 1.0, 2.0mm File Fit Performance Ring Set Included								62cc	65cc	71cc									
346	3.898	3.622	6.098	1.340	0.945	-4.1cc	407	10.6	10.2	9.5	4032	0.500	0.0025	0.0033	930217698				
347	3.905						410	10.6	10.2	9.6					930217605				
348	3.908						411	10.6	10.2	9.6					930217608				
346	3.898	3.622	6.125	1.314	0.927	-4.1cc	406	10.6	10.2	9.5	4032	0.500	0.0025	0.0033	930217998				
347	3.905						408	10.6	10.2	9.6					930217905				
348	3.908						409	10.6	10.2	9.6					930217908				
347	3.905	4.000	6.125	1.110R	0.927	-6.0cc	413	9.3	9.0	8.5	2618	0.500	0.0036	0.0044	930219005				
348	3.908						414	9.3	9.0	8.5					930219008				
383	3.905	4.000	6.125	1.110R	0.927	-6.0cc	400	11.3	11.0	10.3	2618	0.500	0.0036	0.0044	930219705				
384	3.908						401	11.4	11.0	10.3					930219708				
383	3.905						383	10.4	10.0	9.5					2618	0.500	0.0036	0.0044	930219805
384	3.908	4.000	6.125	1.105	0.927	-6.0cc	384	10.4	10.1	9.5	4032	0.500	0.0025	0.0033	930219808				
383	3.905						386	11.3	11.0	10.3					4032	0.500	0.0025	0.0033	930219205
384	3.908						387	11.4	11.0	10.3					387	11.4	11.0	10.3	930219208
383	3.905	4.000	6.125	1.105R	0.927	-26.0cc	383	9.2	8.9	8.5	2618	0.500	0.0036	0.0044	930219405				

Compression Heights with "R" INCLUDE Oil Support Rails

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942