

LT 6.2 Flat Top PowerPak Piston Kit



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio		Alloy	Clearance Guide Meas.		Min	Max	Part No.	
LT 6.2L FLAT TOP - compatible with GM LT1 / L86 / LT4 heads																
1.0, 1.0, 2.0mm File Fit Performance Ring Set Included											60cc	65.5cc				
376	4.065	3.622	6.125	1.304	0.927	-4.5cc	481	11.6	10.8	2618	0.500	0.0046	0.0054		930228765 *	
377	4.070						483	11.6	10.8						930228770 *	
379	4.080						485	11.6	10.9						930228780 *	
415	4.065	4.000	6.125	1.105	0.927	-4.3cc	439	12.7	11.9	2618	0.500	0.0046	0.0054		930165365 *	
416	4.070						441	12.7	11.9						930165370 *	
428	4.125						455	-6.1cc	12.7						11.9	2618
429	4.130	457	12.7	11.9	930173230 *											

*2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications, designed for aftermarket rods

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

