

LT 6.2 Inverted Dome PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide Meas.	Min	Max	Part No.	
LT 6.2L INVERTED DOME - compatible with GM LT1 / L86 / LT4 heads														
1.0, 1.0, 2.0mm File Fit Performance Ring Set Included										60cc	65.5cc			
376	4.065	3.622	6.125	1.304	0.927	-16.0cc	440	10.1	9.6	2618	0.500	0.0046	0.0054	930228365 *
377	4.070						442	10.1	9.6					930228370 *
416	4.070	4.000	6.125	1.105	0.927	-21.6cc	409	10.5	9.9	2618	0.500	0.0046	0.0054	930228070 *
418	4.080						412	10.5	10.0					930228080 *

*2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications, designed for aftermarket rods

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

