

Small Block Chevy 22°/23° Flat Top Gasported PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide			Part No.	
								58cc	64cc	70cc		Meas.	Min	Max		
SMALL BLOCK CHEVY 22°/23° FLAT TOP Gasported																
1.0, 1.0, 2.0mm File Fit Performance Ring set included																
374	4.125	3.500	6.000	1.250	0.927	-7.8cc	453	11.3	10.5	9.9	2618	0.500	0.0061	0.0069	197756525	
375	4.130							455	11.3	10.5					9.9	197756530
376	4.135							457	11.3	10.6					9.9	197756535
377	4.140							459	11.3	10.6					9.9	197756540
378	4.145							461	11.4	10.6					9.9	197756545
379	4.150							463	11.4	10.6					9.9	197756550
380	4.155							464	11.4	10.6					10.0	197756555
381	4.160							466	11.4	10.7					10.0	197756560
381	4.165							468	11.5	10.7					10.0	197756565

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

MAHLE
Motorsport