

SBC 23° Dome PowerPak



SBC 23° Dome PowerPak with Rail



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide			Part No.				
								58cc	64cc	70cc		Meas.	Min	Max					
SMALL BLOCK CHEVY 23° DOME Gasported / Asymmetrical Valve Pockets PowerPak Plus																			
1.0, 1.0, 2.0mm File Fit Performance Ring Set Included																			
357	4.030	3.500	6.000	1.250	0.927	12.0cc	474	14.5	13.1	12.0	2618	0.500	0.0055	0.0063	197754130				
359	4.040						478	14.5	13.2	12.1					197754140				
361	4.050						481	14.6	13.2	12.1					197754150				
362	4.060						485	14.6	13.3	12.2					197754160				
374	4.125						482	15.0	13.6	12.5					2618	0.500	0.0055	0.0063	197836025
376	4.135						486	15.1	13.7	12.5					197836035				
378	4.145						490	15.1	13.7	12.6					197836045				
380	4.155						494	15.2	13.8	12.6					197836055				
381	4.165	497	15.2	13.8	12.7	197836065													
385	4.185	505	15.3	13.9	12.8	197836085													
357	4.030	3.500	6.125	1.125	0.927	12.0cc	455	14.5	13.1	12.0	2618	0.250	0.0055	0.0063	197754330				
359	4.040						459	14.5	13.2	12.1					197754340				
361	4.050						463	14.6	13.2	12.1					197754350				
362	4.060						466	14.6	13.3	12.2					197754360				
400	4.125						446	14.3	13.0	12.0					2618	0.250	0.0055	0.0063	197754525
403	4.135						450	14.3	13.1	12.0					197754535				
405	4.145						454	14.4	13.1	12.1					197754545				
407	4.155						457	14.4	13.2	12.1					197754555				
409	4.165	461	14.5	13.2	12.2	197754565													
385	4.185	468	14.6	13.3	12.3	197754585													
383	4.030	3.750	6.000	1.125	0.927	12.0cc	455	15.4	14.0	12.8	2618	0.250	0.0055	0.0063	197754330				
385	4.040						459	15.5	14.0	12.9					197754340				
386	4.050						463	15.5	14.1	12.9					197754350				
388	4.060						466	15.6	14.2	13.0					197754360				
400	4.125						446	15.2	13.9	12.8					2618	0.250	0.0055	0.0063	197754525
403	4.135						450	15.3	13.9	12.8					197754535				
405	4.145						454	15.3	14.0	12.9					197754545				
407	4.155						457	15.4	14.0	12.9					197754555				
409	4.165	461	15.5	14.1	13.0	197754565													
413	4.185	468	15.6	14.2	13.1	197754585													
388	4.125	3.625	6.125	1.062R	0.927	4.0cc	428	13.6	12.5	11.6	2618	0.250	0.0055	0.0063	197754925				
389	4.135						432	13.7	12.6	11.7					197754935				
391	4.145						435	13.8	12.6	11.7					197754945				
393	4.155						439	13.8	12.7	11.8					197754955				
395	4.165						442	13.9	12.7	11.8					197754965				
399	4.185						450	14.0	12.8	11.9					197754985				
388	4.125						442	14.7	13.5	12.4					197754725				
389	4.130						444	14.8	13.5	12.4					197754730				
389	4.135	445	14.8	13.5	12.4	197754735													
390	4.140	447	14.8	13.5	12.5	197754740													
391	4.145	449	14.9	13.6	12.5	197754745													
392	4.150	450	14.9	13.6	12.5	197754750													
393	4.155	452	14.9	13.6	12.5	197754755													
394	4.160	454	14.9	13.6	12.5	197754760													
395	4.165	456	15.0	13.7	12.6	197754765													
396	4.170	458	15.0	13.7	12.6	197754770													
398	4.180	461	15.1	13.7	12.6	197754780													
399	4.185	463	15.1	13.8	12.7	197754785													
388	4.125	3.875	6.000	1.062R	0.927	4.0cc	428	14.5	13.3	12.4	2618	0.250	0.0055	0.0063	197754925				
389	4.135						432	14.6	13.4	12.4					197754935				
391	4.145						435	14.6	13.4	12.4					197754945				
393	4.155						439	14.7	13.5	12.5					197754955				
395	4.165						442	14.7	13.6	12.5					197754965				
399	4.185						450	14.9	13.7	12.6					197754985				
414	4.125						442	15.7	14.3	13.2					197754725				
415	4.130						444	15.7	14.3	13.2					197754730				
416	4.135	445	15.8	14.4	13.2	197754735													
417	4.140	447	15.8	14.4	13.2	197754740													
418	4.145	449	15.8	14.4	13.3	197754745													
419	4.150	450	15.8	14.4	13.3	197754750													
420	4.155	452	15.9	14.5	13.3	197754755													
421	4.160	454	15.9	14.5	13.3	197754760													
422	4.165	456	15.9	14.5	13.4	197754765													
423	4.170	458	16.0	14.6	13.4	197754770													
425	4.180	461	16.0	14.6	13.4	197754780													
426	4.185	463	16.1	14.6	13.5	197754785													
428	4.125	4.000	6.000	1.000R	0.927	6.0cc	422	15.4	14.1	13.0	2618	0.250	0.0055	0.0063	197830025				
429	4.130						424	15.4	14.1	13.1					197830030				
430	4.135						426	15.5	14.2	13.1					197830035				
432	4.145						429	15.5	14.2	13.1					197830045				
433	4.150						431	15.6	14.3	13.2					197830050				
434	4.155						433	15.6	14.3	13.2					197830055				
435	4.160						435	15.6	14.3	13.2					197830060				
436	4.165						437	15.7	14.3	13.2					197830065				
440	4.185	444	15.8	14.5	13.3	197830085													

Compression Heights with "R" INCLUDE Oil Support Rails

Meas. = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

Compression Ratio - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

MAHLE
Motorsport