

# Small Block Chevy 23° Dome PowerPak Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide			Part No.	
SMALL BLOCK CHEVY 23° DOME																
1.0, 1.0, 2.0mm File Fit Performance Ring Set Included											58cc	64cc	70cc			
332	4.030	3.250	5.700	1.675	0.927	5.0cc	485	12.1	11.1	10.0	4032	0.500	0.0025	0.0033	930208930	
333	4.040						489	12.1	11.1	10.1					930208940	
337	4.060						497	12.2	11.2	10.1					930208960	
355	4.030	3.480/3.500	5.700	1.550	0.927	11.1cc	521	14.2	12.9	11.8	2618	0.500	0.0046	0.0054	930207530	
357	4.040						525	14.2	12.9	11.9					930207540	
400	4.125	3.750	5.700	1.425	0.927	4.1cc	515	14.1	13.0	12.0	2618	0.500	0.0046	0.0054	930207825	
407	4.155						527	14.3	13.1	12.1					930207855	
409	4.165						532	14.3	13.2	12.2					930207865	
355	4.030	3.480/3.500	6.000	1.250	0.927	11.1cc	484	14.2	12.9	11.8	2618	0.500	0.0046	0.0054	930207930	
357	4.040						488	14.2	12.9	11.9					930207940	
360	4.060						496	14.3	13.0	12.0					930207960	
377	4.155						524	14.9	13.5	12.4					930208055	
355	4.030	3.480/3.500	6.125	1.125	0.927	11.1cc	470	14.2	12.9	11.8	2618	0.250	0.0046	0.0054	930208130	
357	4.040						474	14.2	12.9	11.9					930208140	
360	4.060						481	14.3	13.0	12.0					930208160	
372	4.125						498	14.7	13.4	12.3	2618	0.250	0.0046	0.0054	930208225	
377	4.155						509	14.9	13.5	12.4					930208255	
379	4.165						513	14.9	13.6	12.5					930208265	
355	4.030					6.0cc	463	13.1	12.0	11.1	2618	0.250	0.0046	0.0054	930208330	
357	4.040						466	13.1	12.0	11.1					930208340	
360	4.060						474	13.2	12.1	11.2					930208360	
372	4.125					4.0cc	478	13.1	12.1	11.2	2618	0.250	0.0046	0.0054	930212525	
377	4.155						490	13.3	12.2	11.3					930212555	
379	4.165						493	13.3	12.3	11.4					930212565	
383	4.030	3.750	6.000	1.125	0.927	11.1cc	470	15.2	13.8	12.7	2618	0.250	0.0046	0.0054	930208130	
385	4.040						474	15.2	13.9	12.7					930208140	
388	4.060						481	15.4	14.0	12.8					930208160	
400	4.125						498	15.8	14.3	13.1	2618	0.250	0.0046	0.0054	930208225	
407	4.155						509	15.9	14.5	13.3					930208255	
409	4.165						513	16.0	14.5	13.3					930208265	
383	4.030					6.0cc	463	14.0	12.8	11.8	2618	0.250	0.0046	0.0054	930208330	
385	4.040						466	14.0	12.9	11.9					930208340	
388	4.060						474	14.2	13.0	12.0					930208360	
400	4.125					4.0cc	478	14.1	12.9	12.0	2618	0.250	0.0046	0.0054	930212525	
407	4.155						490	14.2	13.1	12.1					930212555	
409	4.165						493	14.3	13.1	12.2					930212565	
395	4.030	3.875	6.000	1.062R	0.927	11.1cc	451	15.7	14.2	13.0	2618	0.250	0.0046	0.0054	930208530	
397	4.040						454	15.7	14.3	13.1					930208540	
401	4.060						462	15.8	14.4	13.2					930208560	
414	4.125					4.0cc	459	14.5	13.3	12.4	2618	0.250	0.0046	0.0054	930208625	
420	4.155						470	14.7	13.5	12.5					930208655	
422	4.165						474	14.7	13.6	12.5					930208665	
434	4.155	4.000	6.000	1.000R	0.927	8.0cc	471	16.1	14.7	13.5	2618	0.250	0.0046	0.0054	930208755	
428	4.125					4.0cc	449	15.0	13.7	12.7	2618	0.250	0.0046	0.0054	930208825	
434	4.155						459	15.1	13.9	12.9					930208855	
436	4.165						463	15.2	14.0	12.9					930208865	

Compression Heights with "R" INCLUDE Oil Support Rails

**Meas.** = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.

"Min" and "Max" is the suggested range of clearance over the coating for each application.

**Compression Ratio** - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942