

# Small Block Chevy 23° Dome POWERPAK Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Meas.	Guide Min	Guide Max	Part No.		
<b>SMALL BLOCK CHEVY 23° DOME</b>															
<b>1.0, 1.0, 2.0mm File Fit Performance Ring Set Included</b>								<b>58cc</b>	<b>64cc</b>	<b>70cc</b>					
<b>1.0, 1.0, 2.0mm File Fit Performance Ring Set Included</b>								<b>58cc</b>	<b>64cc</b>	<b>70cc</b>					
332	4.030	3.250	5.700	1.675	0.927	5.0cc	485	12.1	11.1	10.0	4032	0.500	0.0025	0.0033	930208930
333	4.040						489	12.1	11.1	10.1					930208940
337	4.060						497	12.2	11.2	10.1					930208960
400	4.125	3.750	5.700	1.425	0.927	4.1cc	515	14.1	13.0	12.0	2618	0.500	0.0046	0.0054	930207825
407	4.155						527	14.3	13.1	12.1					930207855
409	4.165						532	14.3	13.2	12.2					930207865
355	4.030	3.480/3.500	6.000	1.250	0.927	11.1cc	484	14.2	12.9	11.8	2618	0.500	0.0046	0.0054	930207930
357	4.040						488	14.2	12.9	11.9					930207940
360	4.060						496	14.3	13.0	12.0					930207960
355	4.030	3.480/3.500	6.125	1.125	0.927	11.1cc	470	14.2	12.9	11.8	2618	0.250	0.0046	0.0054	930208130
357	4.040						474	14.2	12.9	11.9					930208140
360	4.060						481	14.3	13.0	12.0					930208160
372	4.125						495	14.7	13.4	12.3	2618	0.250	0.0046	0.0054	930208225
377	4.155						507	14.9	13.5	12.4					930208255
379	4.165						510	14.9	13.6	12.5					930208265
355	4.030					6.0cc	463	13.1	12.0	11.1	2618	0.250	0.0046	0.0054	930208330
357	4.040						466	13.1	12.0	11.1					930208340
360	4.060						474	13.2	12.1	11.2					930208360
372	4.125					4.0cc	478	13.1	12.1	11.2	2618	0.250	0.0046	0.0054	930212525
377	4.155						490	13.3	12.2	11.3					930212555
379	4.165						493	13.3	12.3	11.4					930212565
383	4.030	3.750	6.000	1.125	0.927	11.1cc	470	15.2	13.8	12.7	2618	0.250	0.0046	0.0054	930208130
385	4.040						474	15.2	13.9	12.7					930208140
388	4.060						481	15.4	14.0	12.8					930208160
400	4.125						495	15.8	14.3	13.1	2618	0.250	0.0046	0.0054	930208225
407	4.155						507	15.9	14.5	13.3					930208255
409	4.165						510	16.0	14.5	13.3					930208265
383	4.030					6.0cc	463	14.0	12.8	11.8	2618	0.250	0.0046	0.0054	930208330
385	4.040						466	14.0	12.9	11.9					930208340
388	4.060						474	14.2	13.0	12.0					930208360
400	4.125					4.0cc	478	14.1	12.9	12.0	2618	0.250	0.0046	0.0054	930212525
407	4.155						490	14.2	13.1	12.1					930212555
409	4.165						493	14.3	13.1	12.2					930212565
414	4.125	3.875	6.000	1.062R	0.927	4.0cc	459	14.5	13.3	12.4	2618	0.250	0.0046	0.0054	930208625
420	4.155						470	14.7	13.5	12.5					930208655
422	4.165						474	14.7	13.6	12.5					930208665
428	4.125	4.000	6.000	1.000R	0.927	4.0cc	449	15.0	13.7	12.7	2618	0.250	0.0046	0.0054	930208825
434	4.155						459	15.1	13.9	12.9					930208855
436	4.165						463	15.2	14.0	12.9					930208865

Compression Heights with "R" INCLUDE Oil Support Rails

**Meas.** = The location to measure piston-to-wall clearance, referenced from the bottom of the piston skirt.  
 "Min" and "Max" is the suggested range of clearance over the coating for each application.  
**Compression Ratio** - calculated at zero deck and 0.040" gasket unless otherwise noted

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942