

## Small Block Chevy Flat Top POWERPAK Piston Set



Cubic Inches	Bore	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio			Alloy	Clearance Guide			Part No.
												Meas.	Min	Max	

### SMALL BLOCK CHEVY FLAT TOP

1.0, 1.0, 2.0mm File Fit Performance Ring Set Included

58cc 64cc 70cc

350	4.000	3.480/3.500	5.700	1.550	0.927	-5.0cc	462	11.1	10.3	9.6	4032	0.500	0.0025	0.0033	930200000									
355	4.030						474	11.2	10.4	9.7					930200030									
357	4.040						478	11.2	10.4	9.8					930200040									
360	4.060						486	11.3	10.5	9.8					930200060									
377	4.000	3.750	5.700	1.425	0.927	-5.0cc	448	11.8	11.0	10.3	4032	0.500	0.0025	0.0033	930200100									
383	4.030						460	12.0	11.1	10.4					930200130									
385	4.040						464	12.0	11.2	10.4					930200140									
388	4.060						472	12.1	11.3	10.5					930200160									
400	4.125						476	12.4	11.6	10.8	4032	0.500	0.0025	0.0033	930200225									
407	4.155						488	12.6	11.7	10.9					930200255									
350	4.000						3.480/3.500	6.000	1.250	0.927					-5.0cc	427	11.1	10.3	9.6	4032	0.500	0.0025	0.0033	930200300
350	4.003															428	11.1	10.3	9.6					930200303
351	4.005	429	11.1	10.3	9.6	930200305																		
352	4.010	431	11.1	10.3	9.6	930200310																		
353	4.020	435	11.1	10.4	9.7	930200320																		
354	4.023	436	11.2	10.4	9.7	930200323																		
355	4.025	437	11.2	10.4	9.7	930200325																		
355	4.028	438	11.2	10.4	9.7	930200328																		
355	4.030	438	11.2	10.4	9.7	930200330																		
357	4.040	442	11.2	10.4	9.8	930200340																		
360	4.060	450	11.3	10.5	9.8	930200360																		
372	4.125	454	11.6	10.8	10.1	4032					0.500	0.0025	0.0033	930200425										
377	4.155	466	11.8	10.9	10.2	930200455																		
379	4.165	469	11.8	11.0	10.3	930200465																		
355	4.030	3.480/3.500	6.125	1.125	0.927	-5.0cc					420	11.2	10.4	9.7		4032	0.250	0.0025	0.0033					930200630
357	4.040										423	11.2	10.4	9.8										930200640
360	4.060						430	11.3	10.5	9.8	930200660													
372	4.125						435	11.6	10.8	10.1	4032	0.250	0.0025	0.0033	930200725									
377	4.155						446	11.8	10.9	10.2	930200755													
379	4.165						450	11.8	11.0	10.3	930200765													
383	4.030						420	12.0	11.1	10.4	4032	0.250	0.0003	0.0033	930200630									
385	4.040						423	12.0	11.2	10.4	930200640													
388	4.060						430	12.1	11.3	10.5	930200660													
400	4.125						435	12.4	11.6	10.8	4032	0.250	0.0025	0.0033	930200725									
407	4.155	446	12.6	11.7	10.9	930200755																		
409	4.165	450	12.6	11.7	11.0	930200765																		
395	4.030	3.875	6.000	1.062R	0.927	-5.0cc	406	12.4	11.5	10.7	4032	0.250	0.0025	0.0033	930200830									
397	4.040						411	12.4	11.5	10.8					930200840									
414	4.125						418	12.8	11.9	11.1					4032	0.250	0.0025	0.0033	930200925					
420	4.155						429	13.0	12.1	11.3					930200955									
422	4.165						432	13.0	12.1	11.3					930200965									
428	4.125	4.000	6.000	1.000R	0.927	-5.0cc	408	13.2	12.3	11.5	4032	0.250	0.0025	0.0033	930201125									
434	4.155						419	13.4	12.4	11.6					930201155									
436	4.165						422	13.4	12.5	11.6					930201165									
440	4.185						-6.5cc	419	13.3	12.3					11.5	2618	0.250	0.0046	0.0054	930201285				

Compression Heights with "R" INCLUDE Oil Support Rails

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

**MAHLE**  
Motorsport