

Subaru WRX 2.5L STI PowerPak & PowerPak Plus



Cubic Bore Inches	Stroke	Rod	Comp Height	Pin Diam.	Crown Vol	Wght G	Compression Ratio	Alloy	Clearance Guide			Part No.	
									Meas.	Min	Max		
SUBARU WRX 2.5L STI, FORESTER, LEGACY													
1.0, 1.0, 2.0mm File Fit Performance Ring Set Included													
CR calculated at 0.3mm below deck and 0.6mm head gasket thickness													
										50cc	56cc		
99.50mm	79.0mm	130.5mm	30.7mm	23mm	-19.3cc	398	9.1	8.5	4032	0.250	0.0021	0.0029	930285017
99.75mm						401	9.1	8.5					930285027
100.0mm						405	9.1	8.5					930285037
99.50mm	79.0mm	130.5mm	30.7mm	23mm	-19.3cc	409	9.1	8.5	2618	0.250	0.0031	0.0039	930285117 *
99.75mm						413	9.1	8.5					930285127 *
100.0mm						417	9.1	8.5					930285137 *
99.50mm	79.0mm	130.5mm	30.7mm	23mm	-14.1cc	411	9.6	9.0	4032	0.250	0.0021	0.0029	930285217
99.75mm						414	9.7	9.0					930285227
100.00mm						418	9.7	9.0					930285237

***PowerPak Plus 2618 Alloy & Hard Anodized Top Ring Groove For Extreme Duty Applications**

Have more questions about this product?

Contact MAHLE Motorsport at 888-255-1942

